

austenit

Slit Coil from Stainless Steel

austenit GmbH is a stainless steel service center, where customer service and highest quality are our main priorities. We attach great importance to provide our customers a most professional and solution-orientated advice.

Contact

Administration

Königsallee 60D
40212 Düsseldorf
Germany

Production

Ellerstraße 101
40721 Hilden
Germany

Contact us

E-Mail: info@austenit.de
Telephone: +49 211 / 55555 - 1

 **www.austenit.de**



austenit

Delivery Programme

Stainless slit strips wound in one layer
Thickness range: 0.30 - 4.00 mm
Width range: 6.00 - 1000 mm
COIL ID: 400/508 mm
COIL OD: max 1800 mm

Available Grades

- 1.4016 / AISI 430
- 1.4509 / AISI 441
- 1.4301 / AISI 304
- 1.4307 / AISI 304L
- 1.4541 / AISI 321
- 1.4404 / AISI 316L

Other grades upon request

Finishes

- 1D hot rolled, annealed, pickled, not as smooth as 2B
- 2B cold rolled, annealed, pickled, cold re-rolled, smoother than 1D
- 2R cold rolled, bright annealed, smooth, blank, reflective

Surface Protection

According to your request we can offer slit strip surface protection with

- Paper interleaving
- One-sided foiling
- Foiling on both sides

Available Foiling

- Nitto SPV 224 thermoforming foil
- Nitto SPV 3067 m blue protective film
- Novacel 4224 UV resistant protective film
- Novacel 4105 thermoforming film

Edge Finishes

- Cut edges
- Roll-rounded edges
- Economically chased edges by knife shearing

Bars Produced from Slit Strips

Stainless steel bars are produced on our straightening line from the slit strips in fixed lengths.

The advantage over sheet metal manufactured bars is the flexibility of lengths, as well as the essential tighter width tolerances.

Dimension Range

- Thickness range: 0.5 - 4.0 mm
- Width range: 8.0 - 110 mm
- Lengths: 10,000 mm (max.)

